

10 000-foot ticks: Alaska Coordinate System, zone 4

North American Datum 1983 (NAD 83) is shown by dashed corner ticks. The values of the shift between NAD 27 and NAD 83 for 7.5 minute intersections is given in USGS Bulletin 1875

There may be private inholdings within the boundaries of the National or State reservations shown on this map

Red tint indicates areas in which only landmark buildings are shown Gray land lines represent unsurveyed and unmarked locations predetermined by the Bureau of Land Management, Folio S-13, Seward Meridian

CONTROL ELEVATIONS SHOWN TO THE NEAREST 0.1 METER UTM GRID AND 1993 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET OTHER ELEVATIONS SHOWN TO THE NEAREST METER To convert meters to feet multiply by 3.2808 To convert feet to meters multiply by 3048 COMPLIES WITH U.S. GEOLOGICAL SURVEY STANDARDS FOR SPATIAL ACCURACY-CLASS 2 FOR SALE BY U.S. GEOLOGICAL SURVEY, P.O. BOX 25286, DENVER, COLORADO 80225 A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

