

10 000-foot ticks: Alaska Coordinate System, zone 4

North American Datum 1983 (NAD 83) is shown by dashed corner ticks. The values of the shift between NAD 27 and NAD 83 for 7.5 minute intersections is given in USGS Bulletin 1875

There may be private inholdings within the boundaries of the National or State reservations shown on this map

Folio S-13, Seward Meridian

Red tint indicates areas in which only landmark buildings are shown Gray land lines represent unsurveyed and unmarked locations predetermined by the Bureau of Land Management, CONTROL ELEVATIONS SHOWN TO THE NEAREST 0.1 METER UTM GRID AND 1993 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET COMPLIES WITH US. GEOLOGICAL SURVEY STANDARDS FOR SPATIAL ACCURACY-CLASS 2 FOR SALE BY U.S. GEOLOGICAL SURVEY FAIRBANKS, ALASKA 99701; DENVER, COLORADO 80225; OR RESTON, VIRGINIA 22092 A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

CONTOURS AND ELEVATIONS IN METERS

QUADRANGLE LOCATION

ANCHORAGE (A-8) NE, ALASKA NE/4 ANCHORAGE (A-8) 1:63 360-SCALE QUARDANGLE 61149-B6-TM-025

1979

REVISED 1993

