

10000-foot ticks: Alaska Coordinate System, zone 4

UTM GRID AND 1993 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET North American Datum of 1983 (NAD 83) is shown by dashed corner ticks. The values of the shift between NAD 27 and NAD 83 for 7.5-minute intersections are given in USGS Bulletin 1875

There may be private inholdings within the boundaries of the National or State reservations shown on this map

Swamps, as portrayed, indicate only wetter areas, usually of low relief, as interpreted from aerial photographs

CONTROL ELEVATIONS SHOWN TO THE NEAREST 0.1 METER OTHER ELEVATIONS SHOWN TO THE NEAREST METER

To convert meters to feet multiply by 3.2808 To convert feet to meters multiply by .3048

COMPLIES WITH U.S. GEOLOGICAL SURVEY STANDARDS FOR SPATIAL ACCURACY-CLASS 2 FOR SALE BY U.S. GEOLOGICAL SURVEY FAIRBANKS, ALASKA 99701; DENVER, COLORADO 80225; OR RESTON, VIRGINIA 22092 A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

ANCHORAGE (B-8) NE, ALASKA NE/4 ANCHORAGE (B-8) 1:63 360-SCALE QUADRANGLE 61149-D6-TM-025 1979 REVISED 1993

QUADRANGLE LOCATION

CONTOURS AND ELEVATIONS IN METERS