


Mapped, edited, and published by the Geological Survey
Control by USC&GS and USCE
Hydrography compiled from USC&GS charts H3210 and 8553
(1:194 154 scale)
Topography from aerial photographs by photogrammetric methods 1952
Aerial photographs taken 1950, field annotated 1951.
Map not field checked
Universal Transverse Mercator projection. 1927 North American datum
1000-meter Universal Transverse Mercator grid ticks, zone 5 shown in blue
Land lines printed in gray represent unsurveyed and unmarked locations
pre-determined by the Bureau of Land Management. Folio S16,
Seward Meridian. Dashed land lines indicate approximate locations
Swamps, as portrayed, indicate only the wetter areas,
usually of low relief, as interpreted from aerial photographs
Unchecked elevations are shown in brown and blue

SCALE 1:63 360
1 2 3 4 MILES
3000 6000 9000 12000 15000 18000 21000 FEET
1 2 3 4 5 KILOMETERS



CONTOUR INTERVAL 50 FEET
DOTTED LINES REPRESENT 25 FOOT CONTOURS
DATUM IS MEAN SEA LEVEL
DEPTH CURVES AND SOUNDINGS IN FEET-DATUM IS MEAN LOWER LOW WATER
SHORELINE SHOWN REPRESENTS THE APPROXIMATE LINE OF MEAN HIGH WATER
THE AVERAGE RANGE OF TIDE IS APPROXIMATELY 20 FEET
FOR SALE BY U.S. GEOLOGICAL SURVEY
FAIRBANKS, ALASKA DENVER 25, COLORADO WASHINGTON 25, D.C.
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST



ROAD CLASSIFICATION
Light-duty

KENAI (D-3), ALASKA
N6045-W15045/15X22.5

1951
MINOR REVISIONS 1960

USGS
Historical File
Topographic Division

U.S.G.S.
FILE COPY
TOPOGRAPHIC DIVISION

NOV - 2 1960

2040