DEPARTMENT OF THE INTERIOR
U.S. GEOLOGICAL SURVEY

STATE OF ALABAMA
EUGENE A. SMITH
STATE GEOLOGIST

ALABAMA
EUTAW QUADRANGLE

88°00' 55' 50' 87°45'
33°00' 55' 50' 32°45'
R. 1 E. R. 2 E. R. 3 E.
T. 23 N. T. 22 N. T. 21 N.
1105000 YARDS

ALICEVILLE 18 MI. TUSCALOOSA 20 MI. (Tuscaloosa)
GAINESVILLE 12 MI. LIVINGSTON 20 MI. EPES 10 MI. DEMOPOLIS 20 MI. MOUNDVILLE 15 MI. TUSCALOOSA 35 MI. SAWYERVILLE 3 MI. GREENSBORO 10 MI.

15 Miles

Topography by Lee Morrison, T. T. Ranney, R. J. Belton, and H. B. Smith
Control by U.S. Geological Survey and Corps of Engineers, U.S. Army
Surveyed in 1927

Polyconic projection. North American datum
5000 yard grid based upon U.S. zone system, C

Scale 1/62500
1 mile = 5000 feet = 1 1/2 = 0 = 1 = 2 = 3 = 4 Miles
5000 = 0 = 5000 = 10000 = 15000 = 20000 Feet
1 1/2 = 0 = 1 = 2 = 3 = 4 = 5 Kilometers

Contour interval 20 feet
Datum is mean sea level

APPROXIMATE MEAN DECLINATION, 1927
TRUE NORTH
MAGNETIC NORTH

HARD IMPROVED OR SURFACED ROADS
OTHER MAIN TRAVELED ROADS
1930

EUTAW, ALA.
Edition of 1931.

HISTORICAL FILES
(DO NOT REMOVE)