



122°07'30" R. 2 W. 12 MI. TO CALIF. 34 122°00' 38°15' T. 5 N. 210 000 FEET 122°00' 38°15' T. 5 N. T. 4 N. 12°30' 12°30' 10' 10' T. 4 N. T. 3 N. 170 000 FEET 38°07'30" 122°07'30" R. 2 W. 1970 000 FEET (PORT CHICAGO) 2'30" 2'30" INTERIOR- GEOLOGICAL SURVEY, WASHINGTON, D. C. 38°07'30" 122°00'

Mapped, edited, and published by the Geological Survey
Control by USGS and USC&GS
Topography from aerial photographs by multiplex methods, and by plane-table surveys 1949. Aerial photographs taken 1948
Foresore and offshore features are from USC&GS charts
Polygonic projection. 1927 North American datum
10,000-foot grid based on California coordinate system, zone 2
Red tint indicates area in which only landmark buildings are shown
Dashed land lines indicate approximate location

SCALE 1:24000
1 0 1000 2000 3000 4000 5000 6000 7000 FEET
1 0 1 2 3 4 5 6 7 8 9 10 KILOMETER
CONTOUR INTERVAL 20 FEET
DOTTED LINES REPRESENT 5 FOOT CONTOURS
DATUM IS MEAN SEA LEVEL
DEPTH CURVES IN FEET-DATUM IS MEAN LOWER LOW WATER
SHORELINE SHOWN REPRESENTS THE APPROXIMATE LINE OF MEAN HIGH WATER
THE AVERAGE RANGE OF TIDE IS APPROXIMATELY 5 FEET
THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY, FEDERAL CENTER, DENVER, COLORADO OR WASHINGTON 25, D. C.
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

USCS
Historical File
Topographic Division
ROAD CLASSIFICATION
HARD-SURFACE ALL WEATHER ROADS DRY WEATHER ROADS
Heavy-duty 4 LANE LANE Improved dirt
Medium-duty 4 LANE LANE Unimproved dirt
Loose-surface, graded, or narrow hard-surface
U. S. Route State Route
NAME CHANGED TO FAIRFIELD SOUTH
FAIRFIELD, CALIF.
NE/4 CARQUINEZ 15' QUADRANGLE
N3807.5-W12200/7.5
EDITION OF 1950
FOR OLDER SURVEYS, SEE SUISUN (1:31680)
DEC 12 1950 3190