



Prepared by the U.S. Army Map Service (GUSM), Corps of Engineers, Washington, D.C. Compiled in 1955 from AMS quadrangles 1:25,000 and 1:50,000, 1944-52; USCGS Charts 5101, 1947; 5202, 1940; 5302, 1941; 5020, 1952; and County Highway Maps, 1947-48. Planimetric detail revised by photo-planimetric methods. Horizontal and vertical control by USGS and CE. Map field checked, 1956. Minor corrections by U.S. Geological Survey, 1962.

CONTOUR INTERVAL 200 FEET
WITH SUPPLEMENTARY CONTOURS AT 100 FEET INTERVALS
TRANSVERSE MERCATOR PROJECTION
100,000-foot grid ticks based on California coordinate system, zone 5
10,000-meter Universal Transverse Mercator grid ticks, zone 5 shown in blue

1955 MAGNETIC DECLINATION FOR THIS SHEET VARIES FROM 15°45' EASTERLY FOR THE CENTER OF THE WEST EDGE TO 15°30' EASTERLY FOR THE CENTER OF THE EAST EDGE. MEAN ANNUAL CHANGE IS 0°02' WESTERLY.

FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER 25, COLORADO OR WASHINGTON 25, D.C.

