


Feet	Meters
1	3048
2	6096
3	9144
4	12192
5	15240
6	18288
7	21336
8	24384
9	27432
10	30480

To convert feet to meters multiply by 3048
To convert meters to feet multiply by 3.2808



1. Dryland
2. Wetlands (May be partially submerged at mean high tide)
3. Exposed at mean low tide

Produced by the Geological Survey and the National Ocean Survey
Control by the USGS and NOS/NOAA
Orthophotomaps prepared from aerial photographs taken January 10, 1976. Topography by photogrammetric methods from aerial photographs taken January 1975 and planetable surveys 1977. Field checked 1977. Map edited 1981
Supersedes topographic map dated 1945
Bathymetry compiled by the National Ocean Survey from tide-coordinated hydrographic surveys
Soundings compiled from NOS charts 11402 and 11404
This information is not intended for navigational purposes
Mean low water (dotted) line and mean high water (solid) line compiled by NOS from tide-coordinated aerial photographs
Apparent shoreline (outer edge of vegetation) shown by photoimagery
Projection and 10,000-foot grid ticks: Florida coordinate system, north zone (Lambert conformal conic)
1000-meter Universal Transverse Mercator grid, zone 16 1927 North American Datum
To place on the predicted North American Datum 1983 move the projection lines 21 meters south and 8 meters west as shown by dashed corner ticks
Dotted land lines established by private subdivision of the Forbes Purchase

UTM GRID AND 1981 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

Survey Number	Survey Date	Survey Scale	Survey Line Spacing (Feet, Meters)
H-5797	1935	1:10,000	01-02
H-5818	1935	1:20,000	02-10

QUADRANGLE LOCATION

SCALE 1:24 000

CONTOUR INTERVAL 2 METERS
SUPPLEMENTARY CONTOUR INTERVAL 1 METER
DASHED SUPPLEMENTARY CONTOURS ARE APPROXIMATE
NATIONAL GEODETIC VERTICAL DATUM OF 1929
CONTROL ELEVATIONS SHOWN TO THE NEAREST 0.1 METER
OTHER ELEVATIONS SHOWN TO THE NEAREST 0.5 METER
BATHYMETRIC CONTOUR INTERVAL 1 METER WITH SUPPLEMENTARY 0.5 METER CONTOURS - SOUNDINGS IN METERS
GULF COAST LOW WATER DATUM
THE RELATIONSHIP BETWEEN THE TWO DATUMS IS VARIABLE
THE MEAN RANGE OF TIDE IS APPROXIMATELY 0.7 METERS

BASE MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
BATHYMETRIC SURVEY DATA COMPLIES WITH INTERNATIONAL HYDROGRAPHIC ORGANIZATION (IHO) SPECIAL PUBLICATION 44 ACCURACY STANDARDS AND/OR STANDARDS USED AT THE DATE OF THE SURVEY
FOR SALE BY THE GEOLOGICAL SURVEY, RESTON, VIRGINIA 22092
AND NATIONAL OCEAN SURVEY, ROCKVILLE, MARYLAND 20852
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

NATIONAL OCEAN SURVEY HYDROGRAPHIC SURVEY INDEX

ROAD CLASSIFICATION

Primary highway, hard surface
Secondary highway, hard surface
Trails
Interstate Route
U. S. Route
State Route
County Route
Light-duty road, hard or improved surface
Unimproved road

CONTOURS AND ELEVATIONS IN METERS

BEVERLY, FLA.
N2945-W8452.5/7.5
1981
DMA 4043 IV SW - SERIES V8470

APR 09 1981