



Mapped by the U. S. Corps of Engineers
Edited and published by the Geological Survey
Control by USGS, USC&GS, USCE, and Florida Geodetic Survey
Topography from aerial photographs by photogrammetric methods
Aerial photographs taken 1950
Field check by the Geological Survey 1952
Polyconic projection. 10,000-foot grid ticks based on Florida
coordinate system, west zone
1000-meter Universal Transverse Mercator grid ticks,
zone 17, shown in blue
The difference between 1927 North American Datum and North American
Datum of 1983 (NAD 83) for 7.5-minute intersections is given in USGS
Bulletin 1875. The NAD 83 is shown by dashed corner ticks
Map edited 1987
Rec tint indicates area in which only landmark buildings are shown

Revisions shown in purple and woodland compiled by the Geological Survey
in cooperation with State of Florida agencies from aerial photographs taken
1984 and other sources. This information not field checked
Map edited 1987
Purple tint indicates extension of urban areas

SCALE 1:24,000
1000 0 1000 2000 3000 4000 5000 6000 7000 FEET
1 5 0 1 KILOMETER
CONTOUR INTERVAL 5 FEET
NATIONAL GEODETIC VERTICAL DATUM OF 1929
THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY
DENVER, COLORADO 80225 OR RESTON, VIRGINIA 22092
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

ROAD CLASSIFICATION
Heavy-duty ——— Light-duty ———
Medium-duty ——— Unimproved dirt ———
U. S. Route ——— State Route ———

QUADRANGLE LOCATION
Map photorevised 1990
No major culture or drainage changes observed
Dashed contours in strip mine areas represent conditions
before being mined

LAKE WALES, FLA.
27081-H5-TF-024
PHOTOINSPECTED 1990
1952
PHOTOREVISED 1987
DMA 4639 I NE - SERIES 9847