



Maped by U.S. Coast and Geodetic Survey  
Edited and published by the Geological Survey  
Control by USC&GS (C), Florida Geodetic Survey (F) and USED (E)  
Culture and drainage in part compiled from  
aerial photographs taken 1942 and 1945. Field check 1947  
Topography by Florida Geodetic Survey 1938 and 1939  
revised and supplemented by plane-table methods, USC&GS 1945-1946  
Polyconic projection. 1927 North American datum  
10,000-foot grid based on Florida coordinate system,  
east zone  
4.6 MI. TO U.S. 27  
MIAMI JUNC. U.S. 41 7.7 MI.  
1000-meter Universal Transverse Mercator grid ticks,  
zone 17, shown in blue  
Red tint indicates area in which only  
landmark buildings are shown  
No distinction is made between dwellings, barns,  
commercial and industrial buildings

TRUE NORTH  
MAGNETIC NORTH  
APPROXIMATE MEAN  
DECLINATION, 1947

SCALE 1:24000  
1000 0 1000 2000 3000 4000 5000 6000 7000 FEET  
1 5 10 20 30 40 50 60 70 80 90 100 KILOMETER  
CONTOUR INTERVAL 5 FEET  
DATUM IS MEAN SEA LEVEL  
SHORELINE SHOWN REPRESENTS THE APPROXIMATE LINE OF MEAN HIGH WATER  
THE AVERAGE RANGE OF TIDE IS APPROXIMATELY 2 FEET  
THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS  
FOR SALE BY U. S. GEOLOGICAL SURVEY, WASHINGTON 25, D. C.  
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

USGS  
Historical File  
Topographic Division  
ROAD CLASSIFICATION  
Heavy-duty ——— Light-duty ———  
Medium-duty ——— Unimproved dirt ———  
U. S. Route ——— State Route ———  
NORTH MIAMI, FLA.  
N2552.5-W8007.5/7.5  
1947  
2860