



V501, EDITION 3

Prepared by the U.S. Army Topographic Command (TVSX), Washington, D.C. Compiled in 1957 from United States quadrangles 1:24,000, 1:25,000, and 1:50,000, 1936-53; USGS charts 1943-50. Planimetry revised from aerial photographs taken 1955. Map field checked 1957. Revised by the U.S. Geological Survey 1970.

Selected hydrographic data compiled from USGS charts 1943-50. This information is not intended for navigational purposes.

Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram.

LEGEND

Figures in red denote approximate distances in miles between stars.

POPULATED PLACES

Over 500,000
100,000 to 500,000
25,000 to 100,000
5,000 to 25,000
1,000 to 5,000
Less than 1,000

RAILROADS

Single track
Double or multiple track
Standard gauge
Narrow gauge

BOUNDARIES

State
County
Park or reservation
Spot elevation in feet

ROADS

Primary, all-weather, hard surface
Secondary, all-weather, hard surface
Light-duty, all-weather, hard or improved surface
Fair or dry weather, unimproved surface
Trail
Interchange

Route markers: Interstate, U.S., State

Landmarks: School, Church, Other

Depth curve in feet

Limit of danger, Reef

Seaslane airport

Power line

Foreshore flat

Intermittent or dry stream

Woods brushwood

Marsh or swamp

Scale 1:250,000

5 0 5 10 15 20 25 30 Statute Miles

5 0 5 10 15 20 25 30 Nautical Miles

5 0 5 10 15 20 25 30 Kilometers

CONTOUR INTERVAL 50 FEET
WITH SUPPLEMENTARY CONTOURS AT 25 FOOT INTERVALS
TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 16

1970 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 5° 30' (60 MILES) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 2° 40' (60 MILES) WESTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, WASHINGTON, D.C. 20242

LOCATION DIAGRAM

SECTIONIZED TOWNSHIP

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

GRID ZONE DESIGNATION

16R

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 100 METERS

SAMPLE POINT

1. Read letters identifying 100,000 meter square in which the point lies.
2. Locate true NORTH and true line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself.
3. Estimate tenths from grid line to point.
4. Locate true HORIZONTAL grid line below point and read LARGE figure labeling the line either in the left or right margin, or on the line itself.
5. Estimate tenths from grid line to point.

SAMPLE REFERENCE

16R11111

USGS HISTORICAL FILE TOPOGRAPHIC DIVISION

PENSACOLA, FLA., ALA.
1957
REVISED 1970

STOCK NO. V501XNH165**03