



Prepared by the Army Map Service (KCSK), Corps of Engineers, U.S. Army, Washington, D. C. Compiled in 1956 by photogrammetric methods and from USGS and AMS quadrangles, 1:24,000 and 1:25,000, 1942-48 and USCGS charts, 1:80,000, 1931-55. Control by USGS, USCGS and Florida Geodetic Survey. Map field checked 1956. Limited revision by U. S. Geological Survey 1963.

100,000-foot grids based on Florida coordinate system, east and west zones

10,000-meter Universal Transverse Mercator grid ticks, zone 17, shown in blue

LEGEND

ROAD DATA 1956 PARTIALLY REVISED 1963

Figures in red denote approximate distances in miles between stars

POPULATED PLACES

Over 500,000

100,000 to 500,000

25,000 to 100,000

5,000 to 25,000

1,000 to 5,000

Less than 1,000

RAILROADS

Single track

Double or Multiple track

Standard gauge

Narrow gauge

BOUNDARIES

State

County

Part or reservation

Horizontal control point

Spot elevation in feet

LANDS & LAKES

More than two lanes wide

Two lanes wide; Federal route marker

Hard surface, medium duty

Two lanes wide; State route marker

Improved light duty

Unimproved dirt

Trail

LANDMARKS

School; Church; Other

Death curve in feet

Limit of danger; Reef

Rocks; Awaik; Sunk

Foreshore flat; Mangrove

Intermittent or dry stream

Marsh or swamp

Approximate road alignment

Scale 1:250,000

0 5 10 15 20 Statute Miles

0 5 10 15 20 Kilometers

0 5 10 15 20 Nautical Miles

CONTOUR INTERVAL 50 FEET

WITH SUPPLEMENTARY CONTOURS AT 25 FOOT INTERVALS

TRANSVERSE MERCATOR PROJECTION

1960 MAGNETIC DECLINATION FOR THIS SHEET VARIES FROM 11°10' EASTERLY FOR THE CENTER OF THE WEST EDGE TO 0°00' FOR THE CENTER OF THE EAST EDGE. MEAN ANNUAL CHANGE IS 0°05' WESTERLY

FOR SALE BY U. S. GEOLOGICAL SURVEY, WASHINGTON 25, D. C.

LOCATION DIAGRAM FOR NG 17-5

RELIABILITY DIAGRAM

SECTIONED TOWNSHIP

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

USGS

WEST PALM BEACH, FLORIDA

1956

LIMITED REVISION 1963