


Map by the U. S. Coast and Geodetic Survey under the direction of the Chief of Engineers, U. S. Army, 1943. Control by the U. S. Coast and Geodetic Survey. Planimetry by U. S. C. & G. S. from 1942 air photographs. Planetable topography and field edit by U. S. C. & G. S., 1944. Polyconic projection, North American datum of 1927. Recoverable horizontal control stations of less than third order accuracy are shown by circles.

ROAD CLASSIFICATION 1944
Dependable hard-surface, heavy-duty road. Loose-surface graded, dry-weather road. U. S. route (74)
Secondary hard-surface, all-weather road. Dirt road. State route (26)
More than two lanes indicated by note along road with tick at point of change 3 LANE | 4 LANE
THIS MAP COMPLETES WITH THE NATIONAL STANDARD MAP ACCURACY REQUIREMENTS



CONTOUR INTERVAL 20 FEET
DATUM IS MEAN SEA LEVEL

ONE THOUSAND YARD GRID COMPUTED FROM "GRID SYSTEM FOR PROGRESSIVE MAPS IN THE U. S." ZONE B; U. S. C. & G. S. SPECIAL PUBLICATION NO. 99 IN THE LAST THREE QUARTS OF THE GRID NUMBERS ARE OMITTED.
THE STATE GRIDS ARE INDICATED AT 10,000 FOOT INTERVALS.
NOTE: OFFICERS USING THIS MAP WILL MARK REVISION CORRECTIONS AND ADDITIONS WHICH COME TO THEIR ATTENTION AND MAIL DIRECT TO "THE CHIEF OF ENGINEERS, WASHINGTON, D. C."

Use diagram only to obtain numerical values. To determine magnetic north line, connect the point "M" on the south edge of the map with the value of the angle between grid and magnetic north, as plotted on the degree scale at the north edge of the map.
APPROXIMATE MEAN DECLINATION 1943 ANNUAL MAGNETIC CHANGE 1" INCREASE

WOODLAND CLASSIFICATION
Dense woodland Dense brush
Scattered brush and trees Orchard
Marsh or swamp Low ground, intermittently flooded

SOCRUM, FLA.
N2807.5-W8200/7.5
EDITION OF 1944

HISTORICAL FILES
(DO NOT REMOVE)