



Prepared by the Defense Mapping Agency Topographic Center, Washington, D. C. Compiled in 1955 by photogrammetric methods and from 1:48,000 and 1:125,000-scale maps dated 1931-35. Photographs field annotated 1925. Revised by the U. S. Geological Survey from aerial photographs taken 1974 and other source data. Revised information not field checked. Map edited 1978.

Area covered by dashed light-blue pattern is subjected to controlled inundation.

100,000-foot grids based on Idaho coordinate system, central and east zones, and Montana coordinate system, south zone.

Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram.

ARTHUR H. ROBINSON MAP LIBRARY
University of Wisconsin-Madison
R-4-4-91

U.S. Regional Depository Copy
DO NOT DISCARD

LEGEND

Figures in red denote approximate distances in miles between stars.

POPULATED PLACES

- Over 500,000
- 100,000 to 500,000
- 25,000 to 100,000
- 5,000 to 25,000
- 1,000 to 5,000
- Less than 1,000

ROADS

- Primary, all-weather, hard surface
- Secondary, all-weather, hard surface
- Light-duty, all-weather, hard or improved surface
- Fair or dry weather, unimproved surface
- Trail
- Interchange
- Route markers: Interstate, U.S., State
- Mile
- Landmark: School; Church; Other
- Spot elevation in feet
- Marsh or swamp
- Intermittent or dry stream
- Power line

BOUNDARIES

- International
- State
- County
- Park or reservation
- Standard gauge
- Narrow gauge
- Single track
- Double or Multiple
- Ballroads
- Landing area
- Seaplane airport
- Seaplane anchorage
- Woods brushwood

Scale 1:250,000

20 Statute Miles

30 Kilometers

15 Nautical Miles

CONTOUR INTERVAL 200 FEET
WITH SUPPLEMENTARY CONTOURS AT 100 FOOT INTERVALS

TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 12

1978 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 17°0' (310 MILS) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 17°0' (300 MILS) EASTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092

LOCATION DIAGRAM

WASH NL 11-5	WASH NL 11-6	WASH NL 11-7	WASH NL 11-8	WASH NL 11-9	WASH NL 11-10	WASH NL 11-11	WASH NL 11-12
OREGON NK 11-5	OREGON NK 11-6	OREGON NK 11-7	OREGON NK 11-8	OREGON NK 11-9	OREGON NK 11-10	OREGON NK 11-11	OREGON NK 11-12
OREGON NK 12-5	OREGON NK 12-6	OREGON NK 12-7	OREGON NK 12-8	OREGON NK 12-9	OREGON NK 12-10	OREGON NK 12-11	OREGON NK 12-12
OREGON NK 13-5	OREGON NK 13-6	OREGON NK 13-7	OREGON NK 13-8	OREGON NK 13-9	OREGON NK 13-10	OREGON NK 13-11	OREGON NK 13-12

SECTIONIZED TOWNSHIP

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

GRID ZONE DESIGNATION

100,000 M. SQUARE IDENTIFICATION

TE UE VE
TO UD VU

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 500 METERS

1. Read letters identifying 100,000 meter square in which the point lies.

2. Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either on the top or bottom margin, or on the line itself.

3. Estimate tenths from grid line to point.

4. Locate first HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either on the left or right margin, or on the line itself.

5. Estimate tenths from grid line to point.

EXAMPLE REFERENCE: UG4013

If reporting beyond 10' in any direction, prefix Grid Zone Designation, e.g., 48Q 0000

ONLY THE LARGER figure of the grid number.

EXAMPLE REFERENCE: UG4013

IF REPORTING BEYOND 10' IN ANY DIRECTION, PREFIX GRID ZONE DESIGNATION, e.g., 48Q 0000

DUBOIS, IDAHO; MONTANA

1955
REVISED 1978

U.S. Regional Depository Copy
DO NOT DISCARD

ARTHUR H. ROBINSON MAP LIBRARY
University of Wisconsin-Madison
APR 04 1991

University of Wisconsin-Madison

3700
250
1456