



Prepared by the Defense Mapping Agency Topographic Center, Washington, D. C. Compiled in 1956 by photogrammetric methods and from USGS quadrangles, 1:25,000-scale maps dated 1938. Photography field annotated 1955. Revised by the U. S. Geological Survey from aerial photographs taken 1978 and other source data. Revised information not field checked. Map edited 1979.

100,000-foot grids based on Oregon coordinate system, north zone and Idaho coordinate system, west zone.

Location of geoidetic control established by government agencies is shown on corresponding 1:250,000-scale Geoidetic Control Diagram.

There may be private inholdings within the boundaries of the National or State reservations shown on this map.

LEGEND
Figures in red denote approximate distances in miles between stars

POPULATED PLACES
Over 500,000
100,000 to 500,000
25,000 to 100,000
5,000 to 25,000
1,000 to 5,000
Less than 1,000

ROADS
Primary, all-weather, hard surface
Secondary, all-weather, hard surface
Light-duty, all-weather, hard or improved surface
Fair or dry weather, unimproved surface
Trail
Interchange

RAILROADS
Standard gauge
Narrow gauge
State
County
Park or reservation

Other Symbols:
Landplane airport
Landing area
Seaplane airport
Seaplane anchorage
Woods-brushwood
Mine
Landmark: School, Church, Other
Spot elevation in feet
Marsh or swamp
Intermittent or dry stream
Power line

Scale 1:250,000
0 5 10 15 20 25 30 Statute Miles
0 5 10 15 20 25 30 Kilometers
0 5 10 15 20 25 30 Nautical Miles

**CONTOUR INTERVAL 200 FEET
WITH SUPPLEMENTARY CONTOURS AT 100 FOOT INTERVALS**

TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 11

1979 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 20° (360 MILS) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 19° (350 MILS) EASTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U. S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092

LOCATION DIAGRAM

48°	NL 10.1	NL 11	NL 12	NL 13	NL 14	49°
	WASHINGTON	OREGON	IDAHO	MONTANA	NEVADA	
	NL 10.2	NL 11.1	NL 12.1	NL 13.1	NL 14.1	
	NL 10.3	NL 11.2	NL 12.2	NL 13.2	NL 14.2	
	NL 10.4	NL 11.3	NL 12.3	NL 13.3	NL 14.3	
	NL 10.5	NL 11.4	NL 12.4	NL 13.4	NL 14.4	
	NL 10.6	NL 11.5	NL 12.5	NL 13.5	NL 14.5	
	NL 10.7	NL 11.6	NL 12.6	NL 13.6	NL 14.6	
	NL 10.8	NL 11.7	NL 12.7	NL 13.7	NL 14.7	
	NL 10.9	NL 11.8	NL 12.8	NL 13.8	NL 14.8	
	NL 11.0	NL 11.9	NL 12.9	NL 13.9	NL 14.9	
	NL 11.1	NL 12.0	NL 13.0	NL 14.0		
	NL 11.2	NL 13.0	NL 14.0			
	NL 11.3	NL 14.0				
	NL 11.4					
	NL 11.5					
	NL 11.6					
	NL 11.7					
	NL 11.8					
	NL 11.9					
	NL 12.0					
	NL 12.1					
	NL 12.2					
	NL 12.3					
	NL 12.4					
	NL 12.5					
	NL 12.6					
	NL 12.7					
	NL 12.8					
	NL 12.9					
	NL 13.0					
	NL 13.1					
	NL 13.2					
	NL 13.3					
	NL 13.4					
	NL 13.5					
	NL 13.6					
	NL 13.7					
	NL 13.8					
	NL 13.9					
	NL 14.0					

SECTIONIZED TOWNSHIP

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

GRID ZONE DESIGNATION
11T
100,000 M SQUARE IDENTIFICATION
MA NA
MV NV

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 100 METERS

SAMPLE POINT: MINAUA

- Read letters identifying 100,000 meter square in which the point lies.
- Locate true VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself.
- Locate true HORIZONTAL grid line to the left of point and read LARGE figure labeling the line either in the left or right margin, or on the line itself.
- Estimate tenths from grid line to point.

EXAMPLE: 500000

IGNORE THE SMALLER figure of any grid number; these are for finding the full coordinates for ONLY THE LARGER figure of the grid number.

SAMPLE REFERENCE
NA1345
11TNA1345

USGS AND HISTORICAL MAP ARCHIVES

GRANGEVILLE, ID
ISSN # 0077-6481
1:250,000