



Prepared by the U.S. Army Topographic Command (ASPM), Washington, D.C. Compiled in 1956 by photogrammetric methods from aerial photographs taken 1954. Photographs field annotated 1955. Revised by the U.S. Geological Survey 1970.
Transverse Mercator Projection, 10,000-meter Universal Transverse Mercator grid, zone 11. 100,000-foot grid ticks based on Idaho coordinate system, central and west zones. 1927 North American Datum 1983, move the projection lines 14 meters north and 74 meters west.
Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram.
There may be private inholdings within the boundaries of the National or State reservations shown on this map.

LEGEND

Figures in red denote approximate distances in miles between stars

POPULATED PLACES

Over 500,000
100,000 to 500,000
25,000 to 100,000
5,000 to 25,000
1,000 to 5,000
Less than 1,000

RAILROADS

Standard gauge
Narrow gauge
International
State
County
Park or reservation

ROADS

Primary, all-weather, hard surface
Secondary, all-weather, hard surface
Light-duty, all-weather, improved surface
Fair or dry weather, unimproved surface
Trail
Interchange

Route markers: Interstate, U.S., State

Landmark: School; Church; Other

Spot elevation in feet

Marsh or swamp

Intermittent or dry stream

Power line

Woods: brushwood

Scale 1:250,000

0 5 10 15 20 25 30 Kilometers

0 5 10 15 20 25 30 Statute Miles

CONTOUR INTERVAL 200 FEET
WITH SUPPLEMENTARY CONTOURS AT 100 FOOT INTERVALS

1970 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 18W (330 MILS) EASTERN FOR THE CENTER OF THE WEST EDGE TO 18W (320 MILS) EASTERN FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092

LOCATION DIAGRAM

11° 10' N	11° 11' N	11° 12' N	11° 13' N	11° 14' N	11° 15' N	11° 16' N	11° 17' N	11° 18' N	11° 19' N	11° 20' N	11° 21' N	11° 22' N	11° 23' N	11° 24' N	11° 25' N	11° 26' N	11° 27' N	11° 28' N	11° 29' N	11° 30' N
11° 10' E	11° 11' E	11° 12' E	11° 13' E	11° 14' E	11° 15' E	11° 16' E	11° 17' E	11° 18' E	11° 19' E	11° 20' E	11° 21' E	11° 22' E	11° 23' E	11° 24' E	11° 25' E	11° 26' E	11° 27' E	11° 28' E	11° 29' E	11° 30' E

SECTIONIZED TOWNSHIP

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

GRID ZONE DESIGNATION

11T

100,000 M. SQUARE IDENTIFICATION

NU PU QU

NT PT QT

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 100 METERS

SAMPLE POINT: PINE

1. Read letters identifying 100,000 meter square in which the point lies.
2. Locate first vertical grid line to left of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself.
3. Estimate tenths from grid line to point.
4. Locate first horizontal grid line below point and read LARGE figure labeling the line either in the left or right margin, or on the line itself.
5. Estimate tenths from grid line to point.
6. If reading beyond 10" in any direction, prefix Grid Zone Designation, as:
11TQ3718

HAILEY, IDAHO

1955

REVISED 1970

U.S. GEOLOGICAL SURVEY
NATIONAL MAP DIVISION
JUL 29 1991
4600