



C.H. Birdseye, Chief Topographic Engineer,
W.H. Herron, Division Topographic Engineer,
Topography by E.L. Hain, K.K. Kimball,
A.L. Opdycke, C.W. Stump, Jr., and W.S. Gehres.
Control by U.S. Lake Survey, F.J. McMaugh,
L.E. Tucker, and S.L. Parker.
Surveyed in 1919-1920.

APPROXIMATE MEAN
DECLINATION, 1920

SCALE 1:62,500
CONTOUR INTERVAL 10 FEET
DATUM IS MEAN SEA LEVEL

INTERIOR—GEOLOGICAL SURVEY,
WASHINGTON, D. C.—1958
POLYCONIC PROJECTION, NORTH AMERICAN DATUM,
10,000 FOOT GRID BASED ON ILLINOIS (EAST) AND
WISCONSIN (SOUTH) RECTANGULAR COORDINATE SYSTEM
1000-METER UNIVERSAL TRANSVERSE MERCATOR
GRID TICKS, ZONE 16, SHOWN IN BLUE

ROAD CLASSIFICATION
Heavy-duty — Light-duty
Medium-duty — Unimproved dirt
U.S. Route — State Route

USGS
Historical File
Topographic Division

GRAY'S LAKE, ILL.—WIS.
N 4215—W 8800/15
1920
U.S.G.S.
FILE COPY
TOPOGRAPHIC DIVISION

FOR SALE BY U. S. GEOLOGICAL SURVEY, WASHINGTON 25, D. C.
BY THE STATE GEOLOGICAL SURVEY, URBANA, ILLINOIS
AND BY THE WISCONSIN GEOLOGICAL AND NATURAL HISTORY SURVEY, MADISON 6, WISCONSIN
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

OCT 15 1988