



V501, EDITION 3

Prepared by the U.S. Army Topographic Command (AJBM), Washington, D.C. Compiled in 1954 by photogrammetric methods from aerial photographs taken 1952. Photographs field annotated 1953. Revised in 1974 by the U.S. Geological Survey from aerial photographs taken 1972.

Area covered by dashed light-blue pattern is subject to controlled inundation.

100,000-foot grids based on Indiana coordinate system, west zone, and Illinois coordinate system, east zone.

Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram.

LEGEND

Figures in red denote approximate distances in miles between stars.

POPULATED PLACES

Over 500,000
100,000 to 500,000
25,000 to 100,000
5,000 to 25,000
1,000 to 5,000
Less than 1,000

RAILROADS

Single track
Double or multiple track
Standard gauge
Narrow gauge
Landing area
Seaplane airport
Seaplane anchorage
Park or reservation

ROADS

Primary, all-weather, hard surface
Secondary, all-weather, hard surface
Light-duty, all-weather, hard or improved surface
Fair or dry weather, unimproved surface
Trail
Interchange

BOUNDARIES

International
State
County
Park or reservation

Other features:

Landmark: School, Church, Other, etc.
Spot elevation in feet
Marsh or swamp
Intermittent or dry stream
Power line

Scale 1:250,000

0 5 10 15 20 25 30 Statute Miles

0 5 10 15 20 25 30 Kilometres

0 5 10 15 20 25 30 Nautical Miles

CONTOUR INTERVAL 50 FEET

TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METRE UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 16

1970 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 2° 16' 00" WEST TO 2° 16' 00" EAST FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, RESTON, VIRGINIA 22092

LOCATION DIAGRAM

Grid showing the location of the map sheet within the larger grid of the Eastern United States. The grid is labeled with letters A through Z and numbers 1 through 36.

SECTIONIZED TOWNSHIP

Grid showing the sectionized township. The grid is labeled with letters A through Z and numbers 1 through 36.

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 100 METERS

1. Read letters identifying 100,000 metre square in which the point lies.
2. Locate first vertical line and the left of point and read LARGE figure flanking the line within the 100,000 metre square, or on the line itself.
3. Locate first horizontal line and the top of point and read LARGE figure flanking the line within the 100,000 metre square, or on the line itself.
4. Combine the two figures to give the standard reference.

INDIANAPOLIS, INDIANA, ILLINOIS

USGS
Historical File
Topographic Division

1953
REVISED 1974

JUL 22 1976

STOCK NO. V501XNJ162**03