

( 3 taken 1951. Field checked 1953. Revised 1966

controlled inundation

Polyconic projection. 1927 North American datum 10,000-foot grid based on Kentucky coordinate system, south zone 1000-meter Universal Transverse Mercator grid ticks, zone 16, shown in blue

Fine red dashed lines indicate selected fence and field lines where generally visible on aerial photographs. This information is unchecked Nolin Reservoir boundary from maps by U.S. Corps of Engineers Areas covered by dashed light-blue pattern are subject to

UTM GRID AND 1966 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET Map photoinspected 1979 No major culture or drainage changes observed

0°25' 7 MILS 36 MILS

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092 KENTUCKY GEOLOGICAL SURVEY, LEXINGTON, KENTUCKY 40506 AND KENTUCKY DEPARTMENT OF COMMERCE, FRANKFORT, KENTUCKY 40601 A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

CONTOUR INTERVAL 20 FEET

NATIONAL GEODETIC VERTICAL DATUM OF 1929

\_\_\_\_\_

KENTUCKY QUADRANGLE LOCATION

The difference between 1927 North American Datum and North American Datum of 1983 (NAD 83) for 7.5-minute intersections is given in USGS Bulletin 1875. The NAD 83 is shown by dashed corner ticks

State Route BEE SPRING, KY. SE/4 LEITCHFIELD 15' QUADRANGLE 37086-C3-TF-024 1966 PHOTOINSPECTED 1979 DMA 3758 IV SE-SERIES V853

Unimproved dirt =======