


War Department mapping project.
Under direction of the Chief of Engineers.
Control by the U. S. Coast and Geodetic Survey.
Planimetry compiled from air photographs by U. S. Coast and Geodetic Survey.
Planimetric topography and field edit by U. S. Coast and Geodetic Survey, 1942.
Polyconic projection, North American datum of 1927.
This map complies with the national standard map accuracy requirements.

ROAD CLASSIFICATION 1942

Dependable hard-surface, heavy-duty road.	Loose-surface graded, dry-weather road.	U. S. route
Secondary, hard-surface, all-weather road.	Dirt road.	State route


More than two lanes indicated by note along road with tick at point of change. **3 LANE 1-4 LANE**



CONTOUR INTERVAL 20 FEET
DATUM IS MEAN SEA LEVEL

ONE THOUSAND YARD GRID COMPUTED FROM "GRID SYSTEM FOR PROGRESSIVE MAPS
IN THE U. S. ZONE A. U. S. C. & G. S. SPECIAL PUBLICATION NO. 59
THE LAST THREE DIGITS OF THE GRID NUMBERS ARE OMITTED
THE STATE GRIDS ARE INDICATED AT 10,000 FOOT INTERVALS

NOTE: OFFICERS USING THIS MAP WILL MAKE NECESSARY CORRECTIONS AND ADDITIONS WHICH COME
TO THEIR ATTENTION AND MAIL DIRECT TO "THE CHIEF OF ENGINEERS, WASHINGTON, D. C."



USGS
Historical File
Topographic Division

Recoverable horizontal control stations of less
than third order accuracy are shown by circles.
The Virginia-Maryland boundary follows the low
water line of the Virginia shore, except where
it crosses the inlets.

ST. GEORGE ISLAND, MD.-VA.
N3800-W7622.5/7.5

U. S. G. S.
FILE COPY
Inspection and Editing