

Topography from aerial photographs by multiplex methods Aerial photographs taken 1944. Field check 1948 Hydrography from surveys dated 1885 to 1937

20° 356 MILS

1°01' 18 MILS

UTM GRID AND 1948 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

Polyconic projection. 1927 North American datum 10,000-foot grid based on Maine coordinate system, east zone.

No distinction is made between dwellings, barns, commercial and industrial buildings

Unchecked elevations are shown in brown 1000-meter Universal Transverse Mercator grid ticks, zone 19, shown in blue

1000 0 1000 2000 3000 4000 5000 6000 7000 FEET _ 1 KILOMETER

CONTOUR INTERVAL 20 FEET DATUM IS MEAN SEA LEVEL DEPTH CURVES AND SOUNDINGS IN FEET-DATUM IS MEAN LOW WATER SHORELINE SHOWN REPRESENTS THE APPROXIMATE LINE OF MEAN HIGH WATER THE AVERAGE RANGE OF TIDE IS APPROXIMATELY 12 FEET

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS FOR SALE BY U.S. GEOLOGICAL SURVEY, WASHINGTON, D.C. 20242 A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST Heavy-duty______ <u>+ LANE 16 LANE</u> Improved dirt____ Medium-duty ____ 4 LANE 16 LANE Unimproved dirt ------Loose-surface, graded, or narrow hard-surface U. S. Route O State Route

USGS

HISTORICAL FILE

WHITNEYVILLE, ME. NE/4 COLUMBIA FALLS 15' QUADRANGLE N4437.5-W6730/7.5 1948 TOPOGRAPHIC DIVISION AMS 7473 II NE-SERIES V811

975

OCT 1 1971