



Mapped, edited, and published by the Geological Survey

Control by USGS, USC&GS, and U. S. Lake Survey
Planimetry by photogrammetric methods from aerial photographs
taken 1959. Topography by planetable surveys 1963

Selected hydrographic data compiled from U. S. Lake Survey Chart 52 (1961)
This information is not intended for navigational purposes

Polycyclic projection. 1927 North American datum
10,000-foot grid based on Michigan coordinate system, east zone
1000-meter Universal Transverse Mercator grid ticks,
zone 17, shown in blue

Fine red dashed lines indicate selected fence and field lines where
generally visible on aerial photographs. This information is unchecked

UTM GRID AND 1963 MAGNETIC NORTH
DECLINATION AT CENTER OF SHEET

SCALE 1:24 000
CONTOUR INTERVAL 5 FEET
DATUM IS MEAN SEA LEVEL
DEPTH CURVES AND SOUNDINGS IN FEET—DATUM IS LOW WATER 578.5 FEET

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY, WASHINGTON 25, D. C.
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

USGS
Historical File
Topographic Division



ROAD CLASSIFICATION
Medium-duty ——— Light-duty ———
Unimproved dirt ———
State Route ○

FISH POINT, MICH.
N4337.5—W8330/7.5

1963

AMS 4271 II NE—SERIES V862

AUG 18 1964

2665