



10 Miles
1
1/4
1/2
3/4
1
1 1/4
1 1/2
1 3/4
2
2 1/4
2 1/2
2 3/4
3
3 1/4
3 1/2
3 3/4
4
4 1/4
4 1/2
4 3/4
5
5 1/4
5 1/2
5 3/4
6
6 1/4
6 1/2
6 3/4
7
7 1/4
7 1/2
7 3/4
8
8 1/4
8 1/2
8 3/4
9
9 1/4
9 1/2
9 3/4
10
10 1/4
10 1/2
10 3/4
11
11 1/4
11 1/2
11 3/4
12
12 1/4
12 1/2
12 3/4
13
13 1/4
13 1/2
13 3/4
14
14 1/4
14 1/2
14 3/4
15
15 1/4
15 1/2
15 3/4
16
16 1/4
16 1/2
16 3/4
17
17 1/4
17 1/2
17 3/4
18
18 1/4
18 1/2
18 3/4
19
19 1/4
19 1/2
19 3/4
20
20 1/4
20 1/2
20 3/4
21
21 1/4
21 1/2
21 3/4
22
22 1/4
22 1/2
22 3/4
23
23 1/4
23 1/2
23 3/4
24
24 1/4
24 1/2
24 3/4
25
25 1/4
25 1/2
25 3/4
26
26 1/4
26 1/2
26 3/4
27
27 1/4
27 1/2
27 3/4
28
28 1/4
28 1/2
28 3/4
29
29 1/4
29 1/2
29 3/4
30
30 1/4
30 1/2
30 3/4
31
31 1/4
31 1/2
31 3/4
32
32 1/4
32 1/2
32 3/4
33
33 1/4
33 1/2
33 3/4
34
34 1/4
34 1/2
34 3/4
35
35 1/4
35 1/2
35 3/4
36
36 1/4
36 1/2
36 3/4

C.H. Birdseye, Chief Topographic Engineer.
W.H. Herron, Division Topographic Engineer.
Topography by J.H. Jennings, R.F. Wilcoxon,
E.G. Wingate, and E.C. Burt.
Control by U.S. Coast and Geodetic Survey, J.R. Ellis,
H.S. Senseney, R.B. Steele, and E.C. Bibbee.
Surveyed in 1920-1921.

Scale 62500
Miles
Kilometers
Contour interval 10 feet.
Datum is mean sea level.

Polyconic projection, North American datum.
5000 yard grid based upon U.S. zone system, B.

MARSHALL, MICH.
Edition of 1923
reprinted 1943
N 4215-W 8445/15

USGS
Historical File
Topographic Division

APPROXIMATE MEAN DECLINATION, 1921
ROUTES USUALLY TRAVELED
HARD IMPERVIOUS SURFACES
OTHER SURFACE IMPROVEMENTS
1943
U. S. ROUTE STATE ROUTE

U. S. G. S.
FILE COPY
Imposition 2011 25¢/sq. in.

APR 15 1944 2/30