



Topography by C.L. Sadler, E.L. Hain, R.R. Monbeck, W.B. Upton, Jr., and J.L. Buckmaster  
Control by U.S. Geological Survey  
Surveyed in 1928 and 1930

ROAD CLASSIFICATION  
 Heavy-duty ——— Light-duty ———  
 Medium-duty ——— Unimproved dirt ———  
 U.S. Route      State Route

SCALE 1:62,500  
 0 1 2 3 4 MILES  
 0 3000 6000 9000 12000 15000 18000 21000 FEET  
 0 1 2 3 4 KILOMETERS

CONTOUR INTERVALS 10 AND 20 FEET, (SEE DIAGRAM)  
 590 FOOT CONTOUR ADDED ALONG LAKE SHORE  
 DATUM IS MEAN SEA LEVEL

Polyconic projection. 1927 North American datum  
 10,000-foot grid based on Michigan (Central)  
 rectangular coordinate system  
 1000-meter Universal Transverse Mercator grid ticks,  
 zone 16, shown in blue

MUSKEGON, MICH.  
 N 4300 - W 8600/15  
 1930

FOR SALE BY U.S. GEOLOGICAL SURVEY, WASHINGTON 25, D. C.  
 A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST



FILE COPY  
 OCT 5 1960  
 MAP INFORMATION OFFICE