U. S. G. S.
FILE COPY
Inspection and Editing

SCOTIA 3.3 MI.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

STATE OF MISSOURI
GEOLOGICAL SURVEY AND WATER RESOURCES
EDWARD L. CLARK, STATE GEOLOGIST

MISSOURI
BERRYMAN QUADRANGLE
15-MINUTE SERIES

JUNC. U. S. NO. 66 19 MI.
ANTHONIES MILL 6.4 MI.

(Sullivan 125000)

91°15' 38°00'

R. 3 W. | 290000 FEET | R. 2 W. | R. 1 W.

91°00' 38°00'

T. 38 N.

780000 FEET

ST. JAMES (JUNC. U. S. NO. 66) 24 MI.
STEELVILLE 6.2 MI.

SHIRLEY 4.2 MI.
POTOSI 12 MI.

T. 37 N.

55'

50'

T. 36 N.

(Steelville)

STEELVILLE 12 MI.
CHERRYVILLE 1.6 MI.

(Potosi)

T. 35 N.

1670000 YARDS

700000 FEET

37°45' 91°15' 785000 YARDS

37°45' 91°00' 350000 FEET

(Stone Hill)

(Bridgehill)

SUNLIGHT 5.5 MI.
BELGRADE 9.2 MI.

DILLARD 1 MI.
BIXBY 10 MI.

VIBURNUM (JUNC. STATE NO. 49) 2.6 MI.

GOODWATER 3 MI.

Mapped by the Geological Survey
1932-1934 and 1943
Entire area within the Clark National Forest

Scale 1/62500

1 0 1 2 3 4 Miles

1000 500 0 1000 2000 3000 4000 5000 6000 7000 Yards

1000 0 3000 6000 9000 12000 15000 18000 Feet

1 .5 0 1 2 3 4 5 Kilometers

Contour interval 20 feet

Datum is mean sea level

APPROXIMATE MEAN DECLINATION, 1934
TRUE NORTH
MAGNETIC NORTH

ROAD CLASSIFICATION 1945

Dependable hard-surface heavy-duty road	Dry weather roads
Secondary hard-surface all weather road	Loose-surface graded
	Unsurfaced, graded
	Dirt road
U. S. Route 15	
State Route 26	

More than two lanes indicated along road with tick at point of change 3 LANE | 4 LANE

Polyconic projection. 1927 North American datum
5000 yard grid based on U.S. zone system, C
10000 foot grid based on Missouri (East) rectangular coordinate system
To join Potosi map use dotted projection corners

BERRYMAN, MO.
Edition of 1945

N3745-W9100/15

USGS
Historical File
Topographic Division

U. S. G. S.
FILE COPY

2/25

JAN 24 1946