

C

1

N

Ľ.

V

1



34°30′ 77°15′

A.M.S. V742 AMS 3, 1948.

Prepared under the direction of the Chief of Engineers by the Army Map Service (AM), U. S. Army, Washington, D. C. Copied in 1946 from North Carolina, 1:62,500, AMS, Sheet 5553 II, 1942. Original map compiled from aerial photography by stereophotogrammetric methods. Aerial photography by U. S. Army Air Force, 1942. Horizontal and vertical control by USGS and USC&GS. Scale changed, Universal Transverse Mercator Grid added and marginal data revised, 1946. This map compiles with the national standard map accuracy requirements. Universal Transverse Mercator grid changed from 1,000 yard to 1,000 meter interval, 1948.

A

LEGEND Only landmark buildings are shown in the city of Swansboro. In developed areas, only through roads are classified

in developed areas, only	through roads are classifie
ROAD	DATA 1942
3 LANE 4 LANE	i sant dia india a

		NOAD L	1042			
Hard surface, heavy duty roa more than two lanes wide Hard surface, heavy duty roa two lanes wide; Federal rou Secondary, hard surface, all- two lanes wide; State route RAILROADS	d, ute marker weather road, e marker	(3)	Trail; Unimpro Railroad in sti UNDER COM	, graded, dry-weat ved road reet; Carline in str NSTRUCTION	eet ABAN	
Standard gauge	Single track	Jouble track		Double track		Double track
Narrow gauge						
Single track carline BOUNDARIES International			Double track	carline	_ ++++++++++++++++++++++++++++++++++++	
State		Horizontal	control pt	Intermittent	stream	
County (with monument)		Bench mark	×			Rapids
County subdivision		Spot elevat	ion, feet 168	Rapids; Falls	5	3)
Reservation		Woods	9.54	Large rapids		Falls
Military-reservation	MIL RES		wood _ 200	7	sh	
School; Church		Brushwood		Rocks awas	h at low tide	C * (
Cemetery		Orchard	0000	Wharf, pier	100 M	·
Churchvard		Vinevard		Man-made s	horeline	

