

North American Datum of 1983 (NAD 83) is shown by dashed corner ticks. The values of the shift between NAD 27 and NAD 83 for 7.5-minute intersections are obtainable from National Geodetic Survey NADCON software

0° 53′ 178 MILS 16 MILS UTM GRID AND 2002 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

CONTOUR INTERVAL 20 FEET SUPPLEMENTARY CONTOUR INTERVAL 5 AND 10 FEET (TO CONVERT ELEVATIONS TO THE NORTH AMERICAN VERTICAL DATUM OF 1929 TO CONVERT ELEVATIONS TO THE NORTH AMERICAN VERTICAL DATUM OF 1988, ADD 1 FOOT) TO CONVERT FROM FEET TO METERS, MULTIPLY BY 0.3048



THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS FOR SALE BY U.S. GEOLOGICAL SURVEY, P.O. BOX 25286, DENVER, COLORADO 80225 A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

FEET



QUADRANGLE LOCATION

💭 Interstate Route 🛛 U.S. Route 🔵 State Route