



**LEGEND**

Figures in red denote approximate distances in miles between stars

**ROADS**

- Primary, all-weather, hard surface
- Secondary, all-weather, hard surface
- Light-duty, all-weather, hard or improved surface
- Fair or dry weather, unimproved surface
- Trail
- Grand Coulee Interchange

**RAILROADS**

- Standard gauge
- Narrow gauge
- Double or multiple track

**BOUNDARIES**

- International
- State
- County
- Park or reservation

**POPULATED PLACES**

- Over 500,000
- 100,000 to 500,000
- 25,000 to 100,000
- 5,000 to 25,000
- 1,000 to 5,000
- Less than 1,000

**Other symbols:** Landplane airport, Landing area, Seaplane airport, Woods-brushwood, Landmark: School, Church, Other, Spot elevation in feet, Marsh or swamp, Intermittent or dry stream, Power line

Scale 1:250,000

0 5 10 15 20 Statute Miles

0 5 10 15 20 25 30 Kilometers

0 5 10 15 20 25 30 Nautical Miles

CONTOUR INTERVAL 200 FEET  
WITH SUPPLEMENTARY CONTOURS AT 100 FOOT INTERVALS

TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 11

1970 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 17° (300 MILS) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 16° (290 MILS) EASTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR WASHINGTON, D.C. 20244

USGS NMD HISTORICAL

JAN 24 1966

REC'D FILE COPY

**LOCATION DIAGRAM**

OREGON NK 11-4 NK 11-5 NK 11-7 NK 11-8 NK 11-9 NK 11-10 NK 11-11 NK 11-12	IDAHO NK 11-1 NK 11-2 NK 11-3 NK 11-4 NK 11-5 NK 11-6	UTAH NK 12-1 NK 12-2 NK 12-3 NK 12-4 NK 12-5	NEVADA NK 10-1 NK 10-2 NK 10-3 NK 10-4 NK 10-5 NK 10-6 NK 10-7 NK 10-8 NK 10-9 NK 10-10 NK 10-11 NK 10-12 NK 10-13 NK 10-14 NK 10-15 NK 10-16 NK 10-17 NK 10-18 NK 10-19 NK 10-20 NK 10-21 NK 10-22 NK 10-23 NK 10-24 NK 10-25 NK 10-26 NK 10-27 NK 10-28 NK 10-29 NK 10-30 NK 10-31 NK 10-32 NK 10-33 NK 10-34 NK 10-35 NK 10-36
---	---	---	---

**SECTIONIZED TOWNSHIP**

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

**GRID ZONE DESIGNATION**

11T UTM

**TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 100 METERS**

EXAMPLE POINT: 442000

1. Read letters identifying 100,000 meter square in which the point lies.

2. Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself.

3. Estimate tenths from grid line to point.

4. Locate first HORIZONTAL grid line below point and read LARGE figure labeling the line either in the left or right margin, or on the line itself.

5. Estimate tenths from grid line to point.

6. Combine tenths from grid line to point.

7. If reporting beyond 50' in any direction, prefix Grid Zone Designation, etc.

11T UTM

STOCK NO. V502XNK1112 \* 03