GOLDFIELD

EDITION 5

V502, EDITION 5

Prepared by the U.S. Army Topographic Command (CGSX), Washington, D.C. Compiled in 1956 by photogrammetric methods and from United States quadrangles, 1:50,000, 1952. Planimetry revised from aerial photographs taken 1952. Photographs field annotated 1954. Revised by the U.S. Geological Survey 1973.

Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram

LEGEND

Figures in red denote approximate distances in miles between stars

POPULATED PLACES
- Over 500,000: LOS ANGELES
- 100,000 to 500,000: OMAHA
- 25,000 to 100,000: GALVESTON
- 5,000 to 25,000: Laramie
- 1,000 to 5,000: Grand Coulee
- Less than 1,000: Sun Valley

RAILROADS
- Standard gauge (Single track, Double or Multiple)
- Narrow gauge
- BOUNDARIES: International; State; County; Park or reservation

Landplane airport; Landing area; Seaplane airport; Seaplane anchorage; Woods-brushwood

ROADS
- Primary, all-weather, hard surface
- Secondary, all-weather, hard surface
- Light-duty, all-weather, hard or improved surface
- Fair or dry weather, unimproved surface
- Trail
- Interchange
- Route markers: Interstate, U.S., State

Landmarks: School; Church; Other; Mine; Spot elevation in feet; Marsh or swamp; Intermittent or dry stream; Power line

Scale 1:250,000

5 0 5 10 15 20 Statute Miles

5 0 5 10 15 20 25 30 Kilometers

5 0 5 10 15 Nautical Miles

CONTOUR INTERVAL 200 FEET
WITH SUPPLEMENTARY CONTOURS AT 100 FOOT INTERVALS

TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 11

MAGNETIC VARIATION FOR 1970 IS 16° 00' (280 MILS) EASTERLY OVER THE ENTIRE AREA

FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR WASHINGTON, D.C. 20242

LOCATION DIAGRAM



USGS
Historical File
Topographic Division

SECTIONIZED TOWNSHIPS

6	5	4	3	2	1	
7	8	9	10	11	12	
18	17	16	15	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

15,050

TOWNSHIP OR RANGE LINE

LAND GRANT BOUNDARY

GRID ZONE DESIGNATION: 11S

100,000 M SQUARE IDENTIFICATION

IGNORE the SMALLER figures of any grid number; these are for finding the full coordinates. Use ONLY the LARGER figure of the grid number; example: 410000

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 1000 METERS

SAMPLE POINT: WYODC MINE

1. Read letters identifying 100,000 meter square in which the point lies.
2. Estimate tenths from grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself.
3. Estimate tenths from grid line to point; Estimate tenths from grid line to point:

MM	3
	4
	7
	4

SAMPLE REFERENCE: MM3474

If reporting beyond 10° in any direction, prefix Grid Zone Designation, as: 11SMM3474

GOLDFIELD, NEVADA; CALIFORNIA
1954
REVISED 1970

SEP 24 1974

STOLTS X. NO. 1950 V502 NJ11-8NW

● INTERIOR—GEOLOGICAL SURVEY, WASHINGTON, D.C.—1973