



V502, EDITION 3
 Prepared by the U.S. Army Topographic Command (KCSM), Washington, D.C. Compiled in 1956 by photogrammetric methods from aerial photographs taken 1953-54. Photographs field annotated 1955. Revised by the U.S. Geological Survey 1970.
 Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram.

LEGEND

Figures in red denote approximate distances in miles between stars

POPULATED PLACES

Over 500,000 **LOS ANGELES**

100,000 to 500,000 **OMAHA**

25,000 to 100,000 **GALVESTON**

5,000 to 25,000 **Laramie**

1,000 to 5,000 **Grand Coulee**

Less than 1,000 **Sun Valley**

ROADS

Primary, all-weather, hard surface

Secondary, all-weather, hard surface

Light-duty, all-weather, hard or improved surface

Fair or dry-weather, unimproved surface

Trail

Interchanges

Route markers: Interstate, U.S., State

RAILROADS

Standard gauge

Single track

Double or multiple track

Narrow gauge

BOUNDARIES

International

State

County

Park or reservation

Landmarks: School; Church; Other

Spot elevation in feet

Marsh or swamp

Intermittent or dry stream

Power line

Landplace airport

Landing area

Seaplane airport

Seaplane anchorage

Woods-brushwood

Scale 1:250,000

0 5 10 15 20 25 30 Statute Miles

0 5 10 15 20 25 30 Kilometers

0 5 10 15 20 25 Nautical Miles

CONTOUR INTERVAL 200 FEET
WITH SUPPLEMENTARY CONTOURS AT 100 FOOT INTERVALS

TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 11

1970 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 11°13' (310 MILES) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 17°13' (300 MILES) EASTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR WASHINGTON, D.C. 20242

LOCATION DIAGRAM

OREGON	UTAH	NEVADA	IDAHO
NK 11.1	NK 11.2	NK 11.3	NK 11.4
NK 11.5	NK 11.6	NK 11.7	NK 11.8
NK 11.9	NK 11.10	NK 11.11	NK 11.12
NK 11.13	NK 11.14	NK 11.15	NK 11.16
NK 11.17	NK 11.18	NK 11.19	NK 11.20
NK 11.21	NK 11.22	NK 11.23	NK 11.24
NK 11.25	NK 11.26	NK 11.27	NK 11.28
NK 11.29	NK 11.30	NK 11.31	NK 11.32
NK 11.33	NK 11.34	NK 11.35	NK 11.36
NK 11.37	NK 11.38	NK 11.39	NK 11.40
NK 11.41	NK 11.42	NK 11.43	NK 11.44
NK 11.45	NK 11.46	NK 11.47	NK 11.48
NK 11.49	NK 11.50	NK 11.51	NK 11.52

SECTIONIZED TOWNSHIP

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

GRID ZONE DESIGNATION: 11T

100,000 M. SQUARE IDENTIFICATION

NS	PS	QS
NR	PR	QR

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 200 METERS

SAMPLE POINT **WELLS** **NS** **PR**

1. Read letters identifying 100,000 meter square in which the point lies.
 2. Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself.
 3. Estimate tenths from grid line to point.
 4. Locate first HORIZONTAL grid line below point and read LARGE figure labeling the line either in the left or right margin, or on the line itself.
 5. Estimate tenths from grid line to point.
 If reporting beyond 25' in any direction, prefix Grid Zone Designation, etc.

USGS
HISTORICAL FILE
NATIONAL MAPPING DIVISION

WELLS, NEVADA; UTAH; IDAHO
 1955
 REVISED 1970

STOCK NO. V502XNK119-03

SEP 21 1981
RETURN TO:
USGS AND HISTORICAL MAP ARCHIVE
7500