

THIS AREA IS SHOWN ON THE MORRISBURG MAP (31 B/14 WEST),
SURVEYED IN 1905 AND 1939, SCALE 1:50,000
PUBLISHED BY THE DEPARTMENT OF MINES AND TECHNICAL SURVEYS, OTTAWA

Mapped, edited, and published by the Geological Survey



Control by USGS, USC&GS, USCE, U.S. Lake Survey, and
International Boundary Commission

Topography by photogrammetric methods from aerial photographs
taken 1960. Field checked 1963

Selected hydrographic data compiled from U. S. Lake Survey
Chart 13 (1962). This information is not intended for
navigational purposes

Polyconic projection. 1927 North American datum
10,000-foot grid based on New York coordinate system, east zone
1000-meter Universal Transverse Mercator grid ticks,
zone 18, shown in blue

Fine red dashed lines indicate selected fence and field lines where
generally visible on aerial photographs. This information is unchecked



CONTOUR INTERVAL 10 FEET
DATUM IS MEAN SEA LEVEL
DEPTH CURVES AND SOUNDINGS IN FEET—DATUM IS LOW WATER 239.9 FEET ABOVE
AND 239.7 FEET BELOW IROQUOIS DAM

USGS
Historical File
Topographic Division



ROAD CLASSIFICATION
Heavy-duty ——— Light-duty ———
Medium-duty ——— Unimproved dirt ———
○ State Route

SPARROWHAWK POINT, N. Y.
SE/4 RED MILLS 15' QUADRANGLE
N4445—W7515/7.5

1963

AMS 5973 IV SE—SERIES V821

U.S.G.S.
FILE COPY

FEB 5 1965