KINGSTON

Prepared by the Army Map Service (AM), Corps of Engineers, U.S. Army, Washington, D.C. Copied in 1954 from Canada, 1:250,000, Army Survey Establishment R.C.E., AHQ, Sheet 31C, 1950-51. Limited revision by U.S. Geological Survey 1967

Transverse Mercator Projection. 10,000-meter Universal Transverse Mercator grid, zone 18. 100,000-foot grid ticks based on New York coordinate system, central zone. 1927 North American Datum. To place on the predicted North American Datum 1983, move the projection lines 2 meters south and 23 meters west

Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram

There may be private inholdings within the boundaries of the National or State reservations shown on this map

LEGEND

ROAD DATA 1954 PARTIALLY REVISED 1967

POPULATED PLACES — More than 2 Lanes; Under Construction; 2 Lanes; Less than 2 Lanes; 2 Lanes

Hard surface, all weather road

Hard surface, all weather road

Loose surface, all weather road

RAILROADS — Single track; Multiple track

Normal gauge

Narrow gauge

International boundary

Province or State boundary

District or County boundary

Park or Reservation boundary

Navigation light

Airport

Landing area

Seaplane airport

Woods-brushwood

Approximate road alinement

Loose surface road, less than two lanes wide — All Weather; Dry Weather

Track; Trail

ROUTE MARKERS — National or Federal; Secondary or State (151; M4)

Electric power line

Spot elevation in feet

Depth curves in fathoms

Swamp or Marsh

Reef; Limit of danger

Intermittent stream

Rocks: Awash; Sunken

Foreshore flats — 169 — Mud; Sand

Scale: 1:250,000

5 0 5 10 15 20 Statute Miles

5 0 5 10 15 20 25 30 Kilometers

5 0 5 10 Nautical Miles

CONTOUR INTERVAL 200 FEET

1965 MAGNETIC DECLINATION FROM TRUE NORTH FOR THIS SHEET VARIES FROM 10° (180 MILS) WESTERLY FOR THE CENTER OF THE WEST EDGE TO 12° (210 MILS) WESTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U. S. GEOLOGICAL SURVEY, RESTON, VIRGINIA 22092

LOCATION DIAGRAM



GRID ZONE DESIGNATION: 18T	TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 1000 METERS
100,000 M. SQUARE IDENTIFICATION	SAMPLE POINT: ENTERPRISE
TE UE VE / TD UD VD / 30 40 490	1. Read letters identifying 100,000 meter square in which the point lies:
IGNORE the SMALLER figures of any grid number; these are for finding the full coordinates. Use ONLY the LARGER figure of the grid number; example: 480000	2. Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself: Estimate tenths from grid line to point:
	3. Locate first HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either in the left or right margin, or on the line itself: Estimate tenths from grid line to point:
	SAMPLE REFERENCE: 18UE5124
	If reporting beyond 18° in any direction, prefix Grid Zone Designation, as: 18TUE5124

KINGSTON, ONT., CAN.; N.Y., U.S.

1954

LIMITED REVISION 1967

● INTERIOR—GEOLOGICAL SURVEY, RESTON, VIRGINIA—1981