



Mapped, edited, and published by the Geological Survey  
Control by USGS and USC&GS  
Topography by photogrammetric methods from aerial  
photographs taken 1960. Field checked 1960  
Polyconic projection. 1927 North American datum  
10,000-foot grid based on Ohio coordinate system, south zone  
1000-meter Universal Transverse Mercator grid ticks,  
zone 17, shown in blue  
Fine red dashed lines indicate selected fence and field lines where  
generally visible on aerial photographs. This information is unchecked  
Land lines based on the Ohio River Base. Dotted land lines established  
by private subdivision of the Ohio Company Purchase  
Unlabeled wells are oil wells

UTM GRID AND 1975 MAGNETIC NORTH  
DECLINATION AT CENTER OF SHEET  
To place on the predicted North American Datum 1983,  
move the projection lines 5 meters south and  
13 meters west as shown by dashed corner ticks

SCALE 1:24,000  
1 0 1000 2000 3000 4000 5000 6000 7000 FEET  
1 0 1 2 3 4 5 6 7 8 9 10 KILOMETER  
CONTOUR INTERVAL 20 FEET  
NATIONAL GEODETIC VERTICAL DATUM OF 1929

ROAD CLASSIFICATION  
Heavy-duty ——— Light-duty - - - - -  
Medium-duty - - - - - Unimproved dirt - - - - -  
U.S. Route □ State Route ○  
AMESVILLE, OHIO  
N3922.5-W8152.5/7.5  
1960  
PHOTOREVISED 1975  
DMA 4662 IV NW—SERIES V852

