



Produced by the United States Geological Survey  
Topography compiled 1960. Planimetry derived from imagery taken 1975. Photospectroscopy using imagery dated 1994; no major culture or drainage changes observed. Survey control current as of 1961. Boundaries, other than corporate, verified 1998.  
North American Datum of 1927 (NAD 27). Projection and 10 000-foot ticks: Ohio coordinate system, south zone (Lambert conformal conic).  
1 000-meter Universal Transverse Mercator grid, zone 17  
North American Datum of 1983 (NAD 83) is shown by dashed corner ticks. The values of the shift between NAD 27 and NAD 83 for 7.5-minute intersections are obtainable from National Geodetic Survey NADCON software.  
Land lines based on the Ohio River Base.  
Information shown in purple may not meet USGS content standards and may conflict with previously mapped contours.



SCALE 1:24 000  
CONTOUR INTERVAL 20 FEET  
NATIONAL GEODETIC VERTICAL DATUM OF 1929  
TO CONVERT FROM FEET TO METERS, MULTIPLY BY 0.3048

ROAD CLASSIFICATION  
Primary highway, hard surface  
Secondary highway, hard surface  
Light-duty road, hard or improved surface  
Unimproved road  
Interstate Route  
U. S. Route  
State Route



BEVERLY, OHIO

1994

NIMA 4663 11 SW-SERIES V852

USGS AND HISTORICAL MAP ARCHIVES  
MAY 31 1998  
REC'D FILE COPY

