



V502, EDITION 3
Prepared by the U.S. Army Topographic Command (BEP), Washington, D.C. Compiled in 1956 by photogrammetric methods and from United States quadrangles, 1:62,500, 1940-53. Planimetry revised in part from aerial photographs taken 1953. Photographs field annotated 1955. Revised by the U.S. Geological Survey 1970.
Area covered by dashed light-blue pattern is subject to controlled inundation
Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram

LEGEND

Figures in red denote approximate distances in miles between stars

POPULATED PLACES

Over 500,000
100,000 to 500,000
25,000 to 100,000
5,000 to 25,000
1,000 to 5,000
Less than 1,000

ROADS

Primary, all-weather, hard surface
Secondary, all-weather, hard surface
Light-duty all-weather, hard or improved surface
Fair or dry weather, unimproved surface
Trail
Interchange

RAILROADS

Standard gauge
Narrow gauge
Landplane airport
Landing area
Seaplane airport
Dry lake
Woods/brushwood

BOUNDARIES

International
State
County
Park or reservation

Other

Mine
Landmark: School, Church, Other
Spot elevation in feet
Marsh or swamp
Intermittent or dry stream
Power line

Scale 1:250,000

0 5 10 15 20 25 30 Statute Miles

0 5 10 15 20 25 30 Kilometers

0 5 10 15 20 25 30 Nautical Miles

CONTOUR INTERVAL 200 FEET
WITH SUPPLEMENTARY CONTOURS AT 100 FOOT INTERVALS

TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 11

1970 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 19° (190 MILS) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 15° (150 MILS) EASTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR WASHINGTON, D.C. 20242

LOCATION DIAGRAM

WASHINGTON
MONT.
IDAHO
OREGON
NEVADA
CALIFORNIA

SECTIONIZED TOWNSHIP

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

GRID ZONE DESIGNATION

11T
100,000 M. SQUARE IDENTIFICATION

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 100 METERS

1. Read letters identifying 100,000 meter square in which the point lies.
2. Locate first horizontal grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself.
3. Locate first vertical grid line to point and read LARGE figure labeling the line either in the left or right margin, or on the line itself.
4. Estimate tenths from grid line to point.

SAMPLE REFERENCE

LV4395

STOCK NO. V502NL1110-03