KLAMATH FALLS

V502, EDITION 4

Prepared by the U.S. Army Topographic Command (BEART), Washington, D.C. Compiled in 1955 by photogrammetric methods from aerial photographs taken 1953. Photographs field annotated 1955. Revised by the U.S. Geological Survey 1970.

Location of geodetic control established by government agencies is shown on corresponding 1:250,000 Geodetic Control Diagram

LEGEND

Figures in red denote approximate distances in miles between stars

POPULATED PLACES
- Over 500,000 — LOS ANGELES
- 100,000 to 500,000 — OMAHA
- 25,000 to 100,000 — GALVESTON
- 5,000 to 25,000 — Laramie
- 1,000 to 5,000 — Grand Coulee
- Less than 1,000 — Sun Valley

RAILROADS (Single track / Double or Multiple)
- Standard gauge
- Narrow gauge

BOUNDARIES
- International
- State
- County
- Park or reservation

ROADS
- Primary, all-weather, hard surface
- Secondary, all-weather, hard surface
- Light-duty, all-weather, hard or improved surface
- Fair or dry weather, unimproved surface
- Trail
- Interchange

Route markers: Interstate, U.S., State

Landmarks: School; Church; Other

- Landplane airport
- Landing area
- Seaplane airport
- Dry lake
- Woods-brushwood
- Mine
- Spot elevation in feet
- Marsh or swamp
- Intermittent or dry stream
- Power line

Scale 1:250,000

5 0 5 10 15 20 Statute Miles

5 0 5 10 15 20 25 30 Kilometers

5 0 5 10 15 Nautical Miles

CONTOUR INTERVAL 200 FEET
WITH SUPPLEMENTARY CONTOURS AT 100 FOOT INTERVALS
TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 10

1970 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 19° (340 MILS) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 18½° (330 MILS) EASTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U. S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225 OR WASHINGTON, D. C. 20242

LOCATION DIAGRAM



SECTIONIZED TOWNSHIP

	6	5	4	3	2	1
	7	8	9	10	11	12
	18	17	16	15	14	13
	19	20	21	22	23	24
	30	29	28	27	26	25
	31	32	33	34	35	36

TOWNSHIP OR RANGE LINE

LAND GRANT BOUNDARY

GRID ZONE DESIGNATION: 10T
100,000 M. SQUARE IDENTIFICATION



IGNORE the SMALLER figures of any grid number. these are for finding the full coordinates. Use ONLY the LARGER figure of the grid number. example: 460000

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 1000 METERS

SAMPLE POINT: RANCH

1. Read letters identifying 100,000 meter square in which the point lies: FB
2. Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself. (Estimate tenths from grid line to point: 5)
3. Locate first HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either in the left or right margin, or on the line itself. (Estimate tenths from grid line to point: 8)

SAMPLE REFERENCE: FB5385

If reporting beyond 18° in any direction, prefix Grid Zone Designation, as, . 10TFB5385

● INTERIOR—GEOLOGICAL SURVEY, WASHINGTON, D. C.—1972

KLAMATH FALLS, OREGON; CALIFORNIA
1955
REVISED 1970