



Basic Control by USC&GS, USGS, and TVA  
Topography by Geological Survey from aerial  
photographs by stereophotogrammetric methods  
Field examination by Tennessee Valley Authority, 1943

1" = 24,000'  
TRUE NORTH  
MAGNETIC NORTH  
APPROXIMATE MEAN  
DECLINATION, 1943

Scale 24,000  
0 1 2 Miles  
0 1 2 Kilometers  
10,000 Feet  
5,000 Feet

Contour interval 20 feet  
Datum is mean sea level

FOR SALE BY U. S. GEOLOGICAL SURVEY, WASHINGTON 25, D. C.  
U. S. TENNESSEE VALLEY AUTHORITY, CHATTANOOGA OR KNOXVILLE, TENN.  
AND TENNESSEE DIVISION OF GEOLOGY, NASHVILLE, TENN.  
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

USGS  
HISTORICAL FILE  
TOPOGRAPHIC DIVISION

Polycyclic projection, 1927 North American datum  
10,000 foot grid based on Tennessee  
rectangular coordinate system  
1000-meter Universal Transverse Mercator  
grid ticks, Zone 16, shown in blue  
ROUTES USUALLY TRAVELED  
HARD IMPERVIOUS SURFACES  
OTHER SURFACE IMPROVEMENTS  
U.S. ROUTE STATE ROUTE

ETOWAH, TENN.  
125-SE  
N3515W8430/7.5  
1943

USGS  
FILE COPY  
TOPOGRAPHIC DIVISION

1985  
Frank Grant + Headline

FEB 12 1983