

Mapped and edited by Tennessee Valley Authority
Published by the Geological Survey


Control by NOS/NOAA, USGS, and TVA

Revised by TVA in 1977 by photogrammetric methods
using aerial photographs taken 1975 and by reference to
TVA/USGS quadrangle dated 1966. Map field checked
by TVA, 1978. Map edited 1979.

Polyconic projection, 1927 North American datum
10,000-foot grid based on Tennessee rectangular coordinate system
1000 meter Universal Transverse Mercator Grid, Zone 17
To place on the predicted North American Datum 1983
move the projection lines 7 meters south and
8 meters west as shown by dashed corner ticks

Fine red dashed lines indicate selected fence and field lines
visible on aerial photographs. This information is unchecked

Red tint indicates areas in which only landmark buildings are shown



CONTOUR INTERVAL 20 FEET
NATIONAL GEODETIC VERTICAL DATUM OF 1929

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U.S. GEOLOGICAL SURVEY, RESTON, VIRGINIA 22092
TENNESSEE DIVISION OF GEOLOGY, NASHVILLE, TENN. 37219
U.S. TENNESSEE VALLEY AUTHORITY, CHATTANOOGA, TENN. 37401 OR KNOXVILLE, TENN. 37902
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST



ROAD CLASSIFICATION	
Heavy-duty	Poor motor road
Medium-duty	Wagon and jeep track
Light-duty	Foot trail
U. S. Route	State Route
In developed areas, only through roads are classified	

MARYVILLE, TENN.
N3545-W8352.5/7.5

1979

AMS 4255 IV SW-SERIES V841

RETURN TO:
USGS AND HISTORICAL MAP ARCHIVES



2600