



Control by USCGS, USGS, TVA and WPA
Topography by Geological Survey from aerial
photographs by stereophotogrammetric methods
Field examination by Tennessee Valley Authority, 1941

1" = 24,000 FEET
TRUE NORTH
MAGNETIC NORTH
APPROXIMATE MEAN
DECLINATION, 1941

SCALE 1:24,000
1000 0 1000 2000 3000 4000 5000 6000 7000 FEET
1 KILOMETER
1 MILE
Contour interval 20 feet
Occasional 10 foot contours shown by broken lines
Datum is mean sea level

USGS
HISTORICAL FILE
TOPOGRAPHIC DIVISION

Polyconic projection, 1927 North American datum
10,000 foot grid based on Tennessee
rectangular coordinate system
1000-meter Universal Transverse Mercator grid ticks,
Zone 16 shown in blue
ROUTES USUALLY TRAVELED
HARD IMPERVIOUS SURFACES
OTHER SURFACE IMPROVEMENTS
STATE ROUTE
U.S. ROUTE

TRANQUILLITY, TENN.
124-SW
N3530 W8437.5/7.5

FOR SALE BY U.S. GEOLOGICAL SURVEY, WASHINGTON, D.C. 20242.
U.S. TENNESSEE VALLEY AUTHORITY, CHATTANOOGA OR KNOXVILLE, TENN.,
AND TENNESSEE DIVISION OF GEOLOGY, NASHVILLE, TENNESSEE
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

U.S.G.S.
FILE COPY
TOPOGRAPHIC DIVISION

OCT 1 4 1965
2645