

Mapped, edited, and published by the Geological Survey

Control by USGS and NOS/NOAA


Topography by photogrammetric methods from aerial photographs taken 1968. Field checked 1969

Polyconic projection. 1927 North American Datum 10,000-foot grid based on Utah coordinate system, north zone 1000-meter Universal Transverse Mercator grid ticks, zone 12, shown in blue


Fine red dashed lines indicate selected fence lines

To place on the predicted North American Datum 1983 move the projection lines 11 meters north and 64 meters east as shown by dashed corner ticks

Revisions shown in purple compiled from aerial photographs taken 1981 and other source data. This information not field checked. Map edited 1986



UTM GRID AND 1986 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET



CONTOUR INTERVAL 40 FEET
DOTTED LINES REPRESENT 20-FOOT CONTOURS
NATIONAL GEODETIC VERTICAL DATUM OF 1929



ROAD CLASSIFICATION

- Primary highway, hard surface
- Secondary highway, hard surface
- Light-duty road, hard or improved surface
- Unimproved road
- Interstate Route
- U. S. Route
- State Route

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

BEAR LAKE SOUTH, UTAH
41111-H3-TF-024

1969
PHOTOREVISED 1986
DMA 3767 IV NE-SERIES V897

USGS NMD HISTORICAL MAP
JUN 20 1986
REC'D FILE COPY