


Richfield 1:62,500
Monroe 1:62,500

Mapped, edited, and published by the Geological Survey
Control by USGS and USC&GS

Topography by photogrammetric methods from aerial
photographs taken 1963. Field checked 1966

Polyconic projection. 1927 North American datum
10,000-foot grid based on Utah coordinate system, central zone
1000-meter Universal Transverse Mercator grid ticks,
zone 12, shown in blue

Fine red dashed lines indicate selected fence lines
Areas covered by dashed light-blue pattern
are subject to controlled inundation



SCALE 1:24,000

CONTOUR INTERVAL 40 FEET
DOTTED LINES REPRESENT 20-FOOT CONTOURS
DATUM IS MEAN SEA LEVEL

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR WASHINGTON, D. C. 20242
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

USGS
Historical
Topographic Division

ROAD CLASSIFICATION

- Heavy-duty ———
- Medium-duty ———
- Light-duty - - - - -
- Unimproved dirt - - - - -

U. S. Route (red circle with number)
State Route (black circle with number)

U.S.G.S.
FILE COPY
TOPOGRAPHIC DIVISION

SIGURD, UTAH
N3845—W11152.5/7.5
1966
AMS 3661 IV SW—SERIES V897

2955
001 9 1969