



Scale 1:250,000

0 5 10 15 20 Statute Miles

0 5 10 15 20 25 Kilometers

0 5 10 15 Nautical Miles

LOCATION DIAGRAM

RELIABILITY DIAGRAM

LEGEND

Figures in red denote approximate distances in miles between stars

POPULATED PLACES

- Over 500,000
- 100,000 to 500,000
- 25,000 to 100,000
- 5,000 to 25,000
- 1,000 to 5,000

ROADS

- Primary, all-weather, hard surface
- Secondary, all-weather, hard surface
- Light-duty, all-weather, improved surface
- Fair or dry weather, unimproved surface
- Trail

RAILROADS

- Single track Double or Multiple
- Normal gauge
- Narrow gauge

BOUNDARIES

- International
- State
- County
- Park or reservation
- Spot elevation in feet

Other symbols include: Fishkill, Landmark, School, Church, Other, Depth curve in feet, Limit of danger, Reef, Rocks, Wash, Foreshore flat, Intermittent or dry stream, Marsh or swamp, Woods-brushwood.

Prepared by the U.S. Army Topographic Command (TPC), Washington, D.C. Compiled in 1946 from United States quadrangles, 1:25,000, 1:50,000, and 1:62,500, USCG&S Charts, 1937-43. Planimetry partially revised from aerial photographs taken 1938. Revised by the U.S. Geological Survey 1969.

Selected hydrographic data compiled from USCG&S Charts. This information is not intended for navigational purposes.

100,000-foot grids based on Virginia coordinate system, south zone, and North Carolina coordinate system.

10,000-meter Universal Transverse Mercator grid ticks, zone 18, shown in blue.

Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram.

CONTOUR INTERVAL 100 FEET WITH SUPPLEMENTARY CONTOURS AT 50 FOOT INTERVALS

TRANSVERSE MERCATOR PROJECTION

1965 MAGNETIC DECLINATION FROM TRUE NORTH FOR THIS SHEET VARIES FROM 65° (120 MILS) WESTERLY FOR THE CENTER OF THE WEST EDGE TO 8° (140 MILS) WESTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, WASHINGTON, D.C. 20242