



37° 30' 30" 25' 20' 15' 10' 5' 0' 5' 10' 15' 20' 25' 30' 35'

79° 45' 40' 35' 30' 25' 20' 15' 10' 5' 0' 5' 10' 15' 20' 25' 30' 35'

SALEM 20 MI. NEWCASTLE 23 MI. CATAWBA 10 MI.

CHRISTIANSBURG 30 MI. SALEM 4 MI. NEWCASTLE 23 MI. CATAWBA 10 MI.

CHRISTIANSBURG 30 MI. SALEM 4 MI. NEWCASTLE 23 MI. CATAWBA 10 MI.

BUCHANAN 4 MI. NATURAL BRIDGE 18 MI.

THATTON 9 MI. BEDFORD 14 MI.

MONETA 14 MI.

1:100,000 YARDS

Topography by E.I. Ireland, Fred Graff, Jr., J.M. Rawls, E.V. Holloway, A.G. England, H. Levinson, W.A. Fisher, R.L. Marx, S. Waggener, H.G. Warner, C.H. Price, W.H. Austin, E.H. Cummings, B.H. Yeaman, and J.H. Lycett
Control by U.S. Geological Survey
Surveyed in 1928-1929

U. S. G. S. FILE COPY
Inspection and Editing.

Contour interval 20 feet
Datum is mean sea level

USGS
Historical File
Topographic Division

Polyconic projection. North American datum
5000 yard grid based upon U.S. zone system, B

HARD IMPERVIOUSLY SURFACED ROADS
OTHER MAIN TRAVELED ROADS

MAR 31 1933 (2890)

ROANOKE, VA.
Edition of 1933
2653-0500; 149;