



PRODUCED BY THE U.S. GEOLOGICAL SURVEY
Base map prepared by Defense Mapping Agency by photogrammetric methods and from aerial photographs dated 1953. Field checked 1955. Revised by the U. S. Geological Survey from aerial photographs taken 1978 and other source data. Revised information not field checked. Map edited 1982.
Transverse Mercator Projection. 10,000-meter Universal Transverse Mercator grid, zone 16. 100,000-foot grid ticks based on Wisconsin coordinate system, central and south zones. 1927 North American Datum. To place on the predicted North American Datum 1983, move the projection lines 5 meters north and 9 meters east.
Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram.
There may be private inholdings within the boundaries of the National or State reservations shown on this map.

LEGEND

Figures in red denote approximate distances in miles between stars

POPULATED PLACES

- Over 500,000
- 100,000 to 500,000
- 25,000 to 100,000
- 5,000 to 25,000
- 1,000 to 5,000
- Less than 1,000

ROADS

- Primary, all-weather, hard surface
- Secondary, all-weather, hard or improved surface
- Fair or dry weather, unimproved surface
- Trail
- Interchange
- Route markers: Interstate, U.S., State

RAILROADS

- Standard gauge
- Narrow gauge
- Single track Double or Multiple
- Landplane airport
- Landing area
- Seaplane airport
- Seaplane anchorage
- Park or reservation

BOUNDARIES

- International
- State
- County

Other features:

- Mine
- Spot elevation in feet
- Marsh or swamp
- Intermittent or dry stream
- Power line
- Woods-brushwood

Scale 1:250,000

20 Statute Miles

15 Nautical Miles

CONTOUR INTERVAL 50 FEET

1982 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 1° (20 MILS) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 1° (20 MILS) WESTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U. S. GEOLOGICAL SURVEY, RESTON, VIRGINIA 22092

A.H. ROBINSON
MAP LIBRARY

JUL 22 1993

University of Wisconsin
Madison

LOCATION DIAGRAM

Grid zone designation: 16T

100,000 M. SQUARE IDENTIFICATION

SECTIONIZED TOWNSHIP

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

GRID ZONE DESIGNATION

16T

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 100 METERS

SAMPLE POINT: CLUSTER

1. Read letters identifying 100,000-meter square within the grid line.

2. Locate first VERTICAL grid line to LEFT of point and read LAST figure before the line either in the top or bottom margin, or on the line itself.

3. Estimate tenths from grid line to point.

4. Locate first HORIZONTAL grid line BELOW point and read LAST figure before the line either in the left or right margin, or on the line itself.

5. Estimate tenths from grid line to point.

SAMPLE REFERENCE:

If reporting beyond 10° in any direction, prefix Grid Zone Designation, as: 48Q0000

GREEN BAY, WISCONSIN

1955
REVISED 1982

3700
\$250
.056
copy