



Maped, edited, and published by the Geological Survey  
 Control by USGS and NOS/NOAA  
 Topography by photogrammetric methods from aerial photographs taken 1966. Field checked 1967  
 Polyconic projection. 1927 North American Datum 10,000-foot grid based on Wyoming coordinate system, west zone  
 1000-meter Universal Transverse Mercator grid ticks, zone 12, shown in blue  
 The difference between 1927 North American Datum and North American Datum of 1983 (NAD 83) for 7.5 minute intersections is given in USGS Bulletin 1875. The NAD 83 is shown by dashed corner ticks  
 Fine red dashed lines indicate selected fence lines  
 Land lines are omitted in areas of extensive tract surveys

UTM GRID AND 1967 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET  
 165° 293 MILS  
 0° 03' 1 MIL

SCALE 1:24 000  
 0 1000 2000 3000 4000 5000 6000 7000 FEET  
 0 1 2 3 4 5 KILOMETER

CONTOUR INTERVAL 40 FEET  
 DOTTED LINES REPRESENT 20-FOOT CONTOURS  
 NATIONAL GEODETIC VERTICAL DATUM OF 1929

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS  
 FOR SALE BY U. S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092  
 A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

WYOMING  
 QUADRANGLE LOCATION

ROAD CLASSIFICATION  
 Primary highway, all weather. Light-duty road, all weather, hard surface.  
 Improved surface.  
 Unimproved road, fair or dry weather.  
 U. S. Route

MARSE, WYO.  
 42110-B8-TF-024  
 1967  
 DMA 3868 III NW-SERIES V874

USGS NW HISTORICAL MAP  
 MAY 20 1991  
 RECD FILE 00P